

PLASCON CONCRETE FLOOR PREP

PRODUCT CODE: FCS 1

TECHNICAL DATA SHEET

Product Description	PLASCON CONCRETE FLOOR PREP (FCS 1) is a matt, water-based ultra-durable preparation coat.											
Intended Uses	<ul style="list-style-type: none"> Use as an adhesion promoter for cementitious floor surfaces 											
Features & Benefits	<ul style="list-style-type: none"> High strength bonding between cementitious substrate and Floor Paint. Good water resistance after complete curing Excellent solvent resistance V.O.C. free Odourless. 											
Product Information	Appearance	Matt										
	Colour	White										
	Generic type	Inorganic										
	Solids	Approx. 20% by mass; 15% by volume										
	Practical spreading rate	10 m ² /ℓ (approx)										
	Viscosity at 23 °C	50-60 KU,										
	S G at 23 °C	1,07 kg/ℓ (typical)										
	Flash point	Non flammable										
Application Details	Mixing	Stir thoroughly with a flat wooden, plastic or stainless steel paddle. Caution – do not use aluminium paddle.										
	Method	Brush or Sheepskin roller										
	Thinning	Not recommended, ready for use										
	Cleaning	Water										
	Substrate	Cementitious substrates, brick and stone										
	Application Environment	<table border="1"> <thead> <tr> <th>Surface Temperature</th> <th>Ambient Temperature</th> <th>Relative Humidity</th> </tr> </thead> <tbody> <tr> <td>Min: 10 °C</td> <td>Min: 10 °C</td> <td>Min: 10%</td> </tr> <tr> <td>Max: 40 °C</td> <td>Max: 40 °C</td> <td>Max: 85 %</td> </tr> </tbody> </table>		Surface Temperature	Ambient Temperature	Relative Humidity	Min: 10 °C	Min: 10 °C	Min: 10%	Max: 40 °C	Max: 40 °C	Max: 85 %
Surface Temperature	Ambient Temperature	Relative Humidity										
Min: 10 °C	Min: 10 °C	Min: 10%										
Max: 40 °C	Max: 40 °C	Max: 85 %										
	Drying time	Touch dry	2 h at 23 °C									
		Overcoating	8 h (minimum) at 23 °C									
Storage and Packaging	Store away from direct sun, heat and severe cold. Packaging: 5 ℓ.											
Surface Preparation	<p>To obtain the best performance the surface must be prepared correctly before application. Allow new concrete to cure for at least 4 weeks before painting. Concrete must be thoroughly cleaned before painting</p> <p>1. SMOOTH CONCRETE (unpainted): For all smooth surfaces, particularly steel floated concrete, apply one coat of PLASCON CONCRETE FLOOR PREP (FCS 1). Allow the surface to dry for 8 hours before applying paint.</p> <p>2. CONCRETE SURFACES – (Unpainted e.g. wood floated): Degrease the surface to remove oil, grease and other contaminants by using PLASCON AQUASOLV DEGREASER (GR1). Allow to react for 20 minutes then rinse thoroughly with fresh water using a bristle broom to remove AQUASOLV and all contaminants. Allow to dry for 48 hours. Apply one coat PLASCON CONCRETE FLOOR PREP (FCS 1). Allow to dry for 8 hours.</p> <p>3. CONCRETE SURFACES – (Previously painted with water based paint): Completely strip old paint. Remove all contaminants such as dirt, grease, oil, dust, etc. Sand smooth or glossy surfaces to improve adhesion. Clean thoroughly with POLYCELL SUGAR SOAP POWDER solution using a scrubbing brush. Rinse thoroughly with water and allow to dry</p>											

PLASCON CONCRETE FLOOR PREP

PRODUCT CODE: FCS 1

Application	<ul style="list-style-type: none"> Apply by brush or roller
Caution	<ul style="list-style-type: none"> Avoid painting if rain is expected. In the event of unexpected showers immediately cover all freshly painted areas with polythene sheeting. Avoid painting if temperature is below 10 °C. Great care should be taken not to paint glass, aluminium window and door frames and other metal surfaces with PLASCON CONCRETE FLOOR PREP (FCS 1). Splashes should be wiped off immediately with water. Do not paint any surfaces other than raw cementitious surfaces.
Safety Precautions	<ul style="list-style-type: none"> Skin contact should be strictly avoided. Wear gloves, safety shoes and eye protection. Keep out of reach of children. Do not pour paint down the drain. In case of skin contact, wash with soap and water or a recognised skin cleaner. Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist. Harmful if swallowed. Do not induce vomiting. Seek medical attention. Refer to Material Safety Data Sheet for complete information.

DISCLAIMER:

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LIMITED

CAPE TOWN:

P O Box 42
Eppindust 7475
Tel: (021) 505-2400
Fax: (021) 534-3791

DURBAN:

Private Bag X16
Mobeni 4060
Tel: (031) 451-3200
Fax: (031) 451-3411

GAUTENG:

P.O. Box 4010
Luipaardsvlei 1743
Tel: (011) 951-4500
Fax: (011) 955-2841

PORT ELIZABETH:

P O Box 1594
Port Elizabeth 6000
Tel: (041) 401-1400
Fax: (041) 453-4606

PLASCON ADVISORY SERVICE: 0860 20 40 60